

Please amend the claims as follow (this listing of claims replaces all prior versions):

1 - 2. (Canceled)

3. (Currently Amended) ~~The method of claim 2~~ A method comprising:
identifying a plurality of memory resources for pushing data to and pulling data from a
processing agent;
when pushing data to the processing agent,
using a push bus arbiter to arbitrate requests for use of a push bus by the memory
resources in which the requests for using the push bus are sent from the memory resources, and
pushing the data from the memory resources to the processing agent through the
push bus, the memory resources obtaining access to the push bus based on arbitration by the
push bus arbiter;
when pulling data from the processing agent,
using a pull bus arbiter to arbitrate requests for use of a pull bus by the memory
resources in which the requests for using the pull bus are sent from the memory resources,
executing a context,
issuing a write command,
loading data into an output transfer memory of the processing agent,
setting the output transfer memory to a read-only state, and
pulling the data from the output transfer memory and transferring to the memory
resources through the pull bus, the memory resources obtaining access to the pull bus based on
arbitration by the pull bus arbiter; and
establishing a plurality of contexts on the processing agent and maintaining program
counters and context relative registers;
wherein the processing agent executes a context and issues a read command to a memory controller in a read phase.

4. (Previously Presented) The method of claim 3 wherein the memory controller processes the read command to be sent to one of the memory resources.

5. (Original) The method of claim 4 wherein the context is swapped out if the read data is required to continue the execution of the context.

6. (Previously Presented) The method of claim 5 wherein after the memory controller has completed the processing of the read command, the memory controller pushes the data to an input transfer memory of the processing agent.

7. (Previously Presented) The method of claim 58 wherein after the data has been pushed, the processing agent reads the data in the input transfer register and the processing agent continues the execution of the context.

8-17. (Cancelled)

18. (Currently Amended) ~~The system of claim 17~~ A system comprising:
a plurality of memory resources, each memory resource being associated with a memory controller;
a processing agent to access the memory resources;
a unidirectional push bus to push data from the memory resources to the processing agent;
a push bus arbiter to arbitrate requests for use of the push bus by the memory resources in which the requests for using the push bus are sent from the memory resources, the memory resources obtaining access to the push bus based on arbitration by the push bus arbiter;
a unidirectional pull bus to receive data from the processing agent and to transfer the data to the memory resources;

a pull bus arbiter to arbitrate requests for use of the pull bus by the memory resources in which the requests for using the pull bus are sent from the memory resources, the memory resources obtaining access to the pull bus based on arbitration by the pull bus arbiter; and a plurality of program counters and a plurality of context relative registers, the context relative registers being selected from a group comprising of general purpose registers, inter-programming agent registers, static random access memory (SRAM) input transfer registers, dynamic random access memory (DRAM) input transfer registers, SRAM output transfer registers, DRAM output transfer registers, and local memory registers;

in which the processing agent is to execute a context and issue a read command to a memory controller.

19. (Original) The system of claim 18 in which the memory controller is to process the read command to be sent to the memory resource.

20. (Previously Presented) The system of claim 19 in which the processing agent is to swap the context out if the read command is required to continue to execution of the context.

21. (Previously Presented) The system of claim 20 in which after the read command is processed, the memory controller is to push the data to an input transfer register of the processing agent and the processing agent is to read the data in the input transfer register and to continue the execution of the context.

22-26. (Cancelled)

27. (Currently Amended) The machine-accessible medium of claim [[26]] 28, which when accessed further results in the machine performing operations comprising establishing a plurality of contexts on the processing agent and maintaining program counters and context relative registers.

28. (Currently Amended) ~~The machine-accessible medium of claim 26~~ A machine-accessible medium, which when accessed results in a machine performing operations comprising:

identifying a plurality of memory resources for pushing data to and pulling data from a processing agent, each memory resource being associated with a memory controller;

when pushing data to the processing agent,

using a push bus arbiter to arbitrate requests for use of a push bus by the memory resources in which the requests for using the push bus are sent from the memory resources,

pushing the data from the memory resources to the processing agent through the push bus, the memory resources obtaining access to the push bus based on arbitration by the push bus arbiter; and

when pulling data from the processing agent,

using a pull bus arbiter to arbitrate requests for use of a pull bus by the memory resources in which the requests for using the pull bus are sent from the memory resources, and

pulling data from the output transfer memory and transferring the data to the memory resources through the pull bus, the memory resources obtaining access to the pull bus based on arbitration by the pull bus arbiter;

wherein the processing agent in a read phase executes a context and issues a read command to a memory controller.

29. (Currently Amended) ~~The machine-accessible medium of claim 26~~ A machine-accessible medium, which when accessed results in a machine performing operations comprising:

identifying a plurality of memory resources for pushing data to and pulling data from a processing agent, each memory resource being associated with a memory controller;

when pushing data to the processing agent,

using a push bus arbiter to arbitrate requests for use of a push bus by the memory resources in which the requests for using the push bus are sent from the memory resources, pushing the data from the memory resources to the processing agent through the push bus, the memory resources obtaining access to the push bus based on arbitration by the push bus arbiter; and

when pulling data from the processing agent,

using a pull bus arbiter to arbitrate requests for use of a pull bus by the memory resources in which the requests for using the pull bus are sent from the memory resources, and pulling data from the output transfer memory and transferring the data to the memory resources through the pull bus, the memory resources obtaining access to the pull bus based on arbitration by the pull bus arbiter;

wherein the memory controller processes the read command to be sent to the memory resource and the context is swapped out if the read command is required to continue the execution of the context.

30-32. (Cancelled)

33. (Currently Amended) The method of claim [[1]] 3 wherein the context is swapped out if the write command is required to continue the execution of the context.

34. (Currently Amended) The method of claim 33 wherein issuing a write command comprises issuing a write command to a memory controller, and wherein the memory controller pulls the data from the output transfer memory and the memory controller sends a signal to the processing agent to unlock the output transfer memory.

35. (Previously Presented) The method of claim 34 wherein if the context has been swapped out after the output transfer memory has been unlocked, the context is swapped back in and the processing agent continues the execution of the context.

36 - 42. (Cancelled)

43. (Currently Amended) The method of claim [[1]] 3, wherein the memory resources comprise memory controller channels.

44. (Currently Amended) The system of claim [[13]] 18, wherein the memory resources comprise memory controller channels.

45. (Currently Amended) The machine accessible medium of claim [[26]] 28, wherein the memory resources comprise memory controller channels.

46-49. (Cancelled)

50. (Currently Amended) ~~The method of claim 49, further comprising~~ A method comprising:

identifying a plurality of memory resources for pushing data to and pulling data from a processing agent;

using a push bus arbiter to arbitrate use of a unidirectional push bus by the memory resources in which requests for using the unidirectional push bus are sent from the memory resources;

pushing the data from the memory resources to the processing agent through the push bus, the memory resources obtaining access to the push bus based on arbitration by the push bus arbiter;

using a pull bus arbiter to arbitrate use of a unidirectional pull bus by the memory resources in which requests for using the unidirectional pull bus are sent from the memory resources; and

pulling the data from the processing agent and transferring to the memory resources through the pull bus, the memory resources obtaining access to the pull bus based on arbitration by the pull bus arbiter; and

executing a context and issuing a read command to a memory controller to read data from one of the memory resources.

51. (Previously Presented) The method of claim 50, further comprising swapping out the context if the data to be read is required to continue the execution of the context.

52. (Canceled)

53. (Currently Amended) The method of claim [[49]] 50, further comprising executing a context and issuing a write command to a memory controller to write data to one of the memory resources.

54. (Previously Presented) The method of claim 53, further comprising swapping out the context if completion of the write command is required to continue the execution of the context.

55 - 56. (Canceled)

57. (Currently Amended) The method of claim [[1]] 3 wherein the output transfer memory comprises an output transfer register.

58. (Previously Presented) The method of claim 6 wherein the input transfer memory comprises an input transfer register.

59. (Currently Amended) The machine-accessible medium of claim [[26]] 28 wherein the output transfer memory comprises an output transfer register.

60 - 61. (Canceled)

62. (Currently Amended) The system of claim [[13]] 18 wherein the memory resources comprise random access memory devices.

63. (Currently Amended) The system of claim [[13]] 18 wherein each of the requests for use of the push bus or pull bus sent from the memory resources comprises a target identifier identifying a target to receive data pushed from or pulled to the memory resources.

64. (Currently Amended) The method of claim [[49]] 50 wherein the memory resources comprise random access memory devices.

65. (Currently Amended) The method of claim [[49]] 50 wherein each of the requests for use of the push bus or pull bus sent from the memory resources comprises a target identifier identifying a target to receive data pushed from or pulled to the memory resources.